



## 4" Level gauge, FAS type

Please indicate dimensions (container diameter and shaft length) when ordering. LLevel gauges for other media on request.

Level gauge, **type W 709**, FAS brand, with 4 "scale, for horizontal, cylindrical containers, spiral seal 1.4571 / graphite up to 550 ° C and screws M12 x 25 mm made of stainless steel, pressure part PN 40 (flange) made of stainless steel 1.4541 , suitable for propane / butane

**Installation position: horizontal**

**Execution A:** bolt holes mounting flange span centre line  
(Standard execution)

**Execution B:** bolt holes mounting flange centre line

Order-No.	Order-No.	Container Ø [mm]	Shaft length [mm]
<b>18 102 1</b>	<b>18 102 4</b>	bis 2000	610
<b>18 102 2</b>	<b>18 102 5</b>	bis 2500	610
<b>18 102 3</b>	<b>18 102 6</b>	bis 3000	610

18 102 9 Additional price - version with spring

**Documentation:** EU declaration of conformity according to the Pressure Equipment Directive

Level gauge, **type S 709**, FAS brand, with 4 "scale, for horizontal, cylindrical containers, spiral seal 1.4571 / graphite up to 550 ° C and screws M12 x 25 mm made of stainless steel, pressure part PN 40 (flange) Stainless steel 1.4541, suitable for propane / butane

**Installation position: vertical**

**Execution A:** bolt holes mounting flange span centre line  
(Standard execution )

**Execution B:** bolt holes mounting flange centre line

Order-No.	Order-No.	Container Ø [mm]	Schaft length [mm]
<b>A</b>	<b>B</b>		
<b>18 103 1</b>	<b>18 103 4</b>	to 2000	Please indicate
<b>18 103 2</b>	<b>18 103 5</b>	to 2500	
<b>18 103 3</b>	<b>18 103 6</b>	to 3000	

**Documentation:** EU declaration of conformity according to the Pressure Equipment Directive